

Durain FR Ecogreen Rain Jacket
TILFRHYDRJ

DESCRIPTION

TIL Durain FR EcoGreen Rain Jacket made from 270g/m² Hydro-Control fabric. Provides flame retardant protection combined with waterproof performance for outdoor FR work environments.

KEY FEATURES

- Durable
- Ecogreen
- Flame Resistant
- Waterproof

DETAILED FEATURES

- 270g/m² Hydro-Control FRC fabric
- Flame retardant and waterproof combination
- TIL WORKWEAR branded design
- Eco-friendly FR materials
- Durable construction for harsh environments
- Suitable for outdoor FR work applications

APPLICATIONS

- Outdoor Oil & Gas operations
- Offshore work in wet conditions
- Petrochemical outdoor work
- Electrical utilities in rain
- Construction in wet environments
- General FR work in rain/wet conditions



Hi-visibility Saturn Yellow
Code: HVS



OTHER COLORS



Navy Blue

PRODUCT INFORMATION

Category:

Workwear

Available Sizes:

S, M, L, XL, 2XL, 3XL, 4XL

PACKAGING WASTE						
Material	Type	Unit	Weight (g)	Length (mm)	Width (mm)	Height (mm)
Cardboard	Outer	1	0.05	0.716	0.232	0.414
Plastic	Inner	1	0.01	0.5	0.4	0.0
Paper	Inner	1	0.002	0.21	0.148	0.0



Durain FR Ecogreen Rain Jacket

TILFRHYDRJ

Technical Data

Parameter	Specification	Standard / Test Method
Product Code	TILFRHYDRJ	
Width	150 cm (+2/-1 cm)	ISO 3801:1978
Weight	200g/m ² (±5%)	ISO 3932:1980
Composition	Modacrylic/lyocell/para-aramid/Static-Control™ + PU film	
Construction	2/1 twill	
Available finishes	Standard: Hydro-Tec. Optional: Comfort	

Physical Performance

Parameter	Specification	Standard / Test Method
Tensile Strength	900 N x 650 N (± 10%)**	ISO 13934-1:1999

Care Labelling

Parameter	Specification	Standard / Test Method
Domestic Laundering	    	
PPE Requirements	      optional: 	

Certifications

Icon	Specification	Standard / Test Method
	Foul Weather	EN 343: 2019
	Industrial flame and heat hazards	EN ISO 11612 A1, A2, B1, C1: 2015
	Short-duration thermal exposures from fire	NFPA 2112: 2018
	Electric Arc	Single Layer: EN IEC 61482-1-2, class 1; 2015 HRC/Category 1 (4 ≤ATPV ≥ 8 cal/cm2) System: XL9200 + XL9240 EN IEC 61482-1-2; 2015 class 2 (7kA) System: HRC/Category 2 (8 ≤ATPV ≥ 25 cal/cm2)
	Anti-Static for explosion risk	EN 1149-5: 2018, EN 1149-3: 2004
	Liquid chemicals **	EN 13034: 2005 + A1: 2009
	High Visibility Colour: Yellow Contrast colours: Twilight 89250	EN ISO 20471: 2013
	General requirements***	EN ISO 13688: 2013
	Öko-Tex Standard 100, class 2	Centexbel, no. 0903009



All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. PARKER Coverall declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.

